



Satellite Set

KB59



Electrical and Mechanical characteristics

Fréquence (GHz)	10-13
Dish dimension (mm)	530 X 600
Gain @ 10,75 GHz (dB)	33,50
Gain @ 11,75 GHz (dB)	34,80
Gain @ 12,75 GHz (dB)	35,40
Second lobe discrimination (dB)	> 27
Elevation with passing mast	Oui
F/D Ratio	0,64
Opening angle at 12.75 GHz (deg)	< 3
Operational elevation (deg)	15 - 50
pointing offset angle (deg)	28
Mast diameter (mm)	32 - 50
Windloading @ 72 km/h (kg)	10
Windloading @ 144 km/h (kg)	40
Windloading @ 216 km/h (kg)	90
Pré-mounting mount	No
Dish material	Steel
Section of the aluminium bracon (mm)	25 x 15

Product advantages ...

- Ultra fast assembly
- Polypropylène mount
- Aluminium Bracon
- 2 stripups mount
- 13 mm hexagon nuts

Set composition ...

- 1 SB59 dish (60 cm)
- 1 UST100 LNB
- 1 double fluted box

logistic Info ...

- Référence : KB59
- Packaging : 1 set = 1 carton
- 1 pallet = 40 sets



Hot Line **0 899 707 205** Service 0,80 € / min
+ prix appel

www.servimat.fr