



### PACKAGING

- Référence : UST400
- Carton of 50p
- 53 x 29 x 33,5 cm - 15,5 k

## TECHNICAL CHARACTERISTICS\*

### Spécifications

### Low band

### High band

INPUT FREQUENCY	10.7 ~ 11.7 GHz	11.7 ~ 12.75 GHz
F/D RATION	0,5 ~ 0,7	
CROSS POLAR ISOLATION	20 dB (Min)	
GAIN NOISE	0.1 dB (Typ)	0.1 dB (Typ)
GAIN	55 dB (Typ)	
BAND GAIN VARIATION	± 0.5 dB / 27 MHz	
OPERATING OUTPUT FREQUENCY	Port 1 : 950 ~ 1950 MHz Port 2 : 1100 ~ 2150 MHz Port 3 : 950 ~ 1950 MHz Port 4 : 1100 ~ 2150 MHz	Horizontal Horizontal Vertical Vertical
OSCILLATOR PLL FREQUENCY	9.75 GHz	10.60 GHz
OSCILLATOR PHASE NOISE	- 55 dB / Hz (@ 1 KHz) - 80 dB / Hz (@ 10 KHz) - 100 dB / Hz (@ 100 KHz)	
OUTPUT POWER (@1 dB gain compression)	0 dB	
PICTURE REJECTION	45 dB	
SWR	2.5 : 1 (Max)	
OUTPUT CONNECTORS	75 Ω F female	
CONSUMPTION	250 mA (Max)	
POWER SUPPLY - 22 KHz	11,5 ~ 14,0 Volts / Vertical polarity 16.0 ~ 19,0 Volts / Horizontal polarity 22 KHz continu (± 4 KHz) High band sélection	
OPERATING TEMPERATURE	40° C ~ + 60° C	

Except where otherwise stated, the values given are only valid for operation under normal temperature and humidity conditions.

\*For the purpose of improvement, technical specifications are subject to change without notice.